

ADSOLVE 6002
TOLUENE**DESCRIPTION**

ADSOLVE 6002 is a toluene based cleaner for equipment and surfaces.

TECHNICAL PROPERTIES

Test	Method	Typical values (*)	Specifications
Flash point	ASTM D56	4	
Density à 15°C (kg / m3)	ASTM D1298 / D4052	871.47	869 – 873

*the values are historical averages only.

PACKAGING

- 18.9 liters
- 200 liters

STORAGE

ADSOLVE 6002 has a shelf life of 12 months when stored in its unopened original packaging in a dry place at a temperature between 15°C and 25°C (59°F et 95°F). Keep from freezing.

CAUTION

Inflammable. Keep away from heat, open flame, spark and pilot lights. Use only under well ventilated conditions. Harmful or fatal if swallowed. Vapour harmful. Avoid splashing in the eyes. Always consult sds before using the product. Apply usual hygienic rules. Always test the product on your application before use. For industrial use only. For more information, please contact your technical representative.

IMPORTANT**READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.