

ADBOND 8223-3
Neoprene base contact adhesive**DESCRIPTION**

ADBOND 8223-3 is a brush grade neoprene rubber base contact adhesive. It adheres very well on laminate, particle board, plywood as well as mdf. It can be used for wood veneer with backer protector. Wait 24 hours before applying lacquer. The first pass of lacquer will have to be sprayed in a thin layer in order to avoid too much solvent which could impair the adhesion of ADBOND 8223-3. Consult your technical representative for more information. ADBOND 8223-3 can also be used for bonding clean sheet metal to plywood.

PHYSICAL PROPERTIES

| | |
|---------------|---|
| Color | Tan |
| Odor | Ketone |
| Viscosity | 400 – 800 cPs @ 25°C |
| Density | 0.79 (kg/L) |
| Solids | 24 – 27 (%) |
| Assembly time | 15 – 45 minutes (Depending on temperature and ambient humidity) |
| Shelf life | 6 months |

METHOD OF USE

Surfaces must be clean and free from dust, grease or other contaminants. Apply ADBOND 8223-3 using a brush or roller in thin layer on both surfaces. Wait 15 to 45 minutes (until it do not transfer to the hand) depending on the temperature and humidity and assemble by pressing the two surfaces together.

APPLICATION

- Countertop
- Laminates bonding
- Decorative panels
- Commercial and residential furniture

STORAGE

6 months from date of production in the original unopened containers. Protect form freezing. Keep in a hermetic closed container to avoid any contamination.

CLEANING

Equipment or overflows can be cleaned with ADSOLVE 6002. Disposal of cleaning solvents and adhesive residues should be sent to a certified hazardous waste disposal company.

ADBOND 8223-3
Neoprene base contact adhesive**CAUTION**

Extremely flammable and harmful. Keep away from sources of heat and sparks. Ensure adequate ventilation during spraying. Always consult sds before using the adhesive. For industrial use only. For more information, please contact your technical representative.

IMPORTANT**READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.