

ADSEAL SETTING BLOCK SETTING BLOCK FOR INSULATED GLASS UNIT

DESCRIPTION

ADSEAL SETTING BLOCK is a setting block made of flexible pvc fully compatible with silicones ADSEAL DWS 4580 SERIES, ADSEAL LM 4600 SERIES and ADSEAL STRUCTURAL 4940 SERIES. ADSEAL SB 20-XXX is made for commercial, institutional or industrial applications on job site or production plant. 3/16", 1/4" and 3/8" dimensions have a groove on the length of the block which promotes the flow of water to drain the window or curtain wall. ADSEAL SETTING BLOCK will not stain the ADSEAL silicone range when used on horizontal 2 sided or 4 sided curtain walls contrary to neoprene or epdm.

PHYSICAL PROPERTIES

Color	Black
Hardness (shore A)	83 – 85
Tolerance	
Length	±0.125"
Width	±0.025"
Thickness	±0.010" (1/16 et 1/8) / ±0.015 (3/16, 1/4, 3/8)

DIMENSIONS

Product code	Dimension (thickness / width / length)	Quantity per box
62.5 x 1.125	1/16" x 1.125" x 4"	1500
125 x 1.125	1/8" x 1.125" x 4"	750
187 x 1.125	3/16" x 1.125" x 4"	700
250 x 1.125	1/4" x 1.125" x 4"	500
375 x 1.125	3/8" x 1.125" x 4"	300

CAUTION

Always test the product on your application before use. For industrial use only. For more information, please contact your technical representative.

IMPORTANT READ CAREFULLY

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.