

ADSEAL PRIMER MK60095**EB PRIMER****DESCRIPTION**

ADSEAL PRIMER MK60095 is a primer designed to increase the adhesive strength of our ADSEAL silicone and hybrid sealants on difficult-to-bond adhere surfaces. ADSEAL PRIMER MK60095 has a volatile organic compound content of 80 g / L that complies with the federal EPA maximum limit of 350 g/L.

The use of ADSEAL PRIMER MK60095 as a primer should not be a substitute for proper preparation and cleaning of surfaces to be sealed or glued. The product should not be applied to painted surfaces or solvent-sensitive plastics. It is recommended to check compatibility with surfaces before use.

LIMITATIONS

This primer will dissolve the expanded polystyrene (EPS) insulation board found within Exterior Insulation and Finish Systems (EIFS). Over application of this product onto EIFS substrates could diminish the integrity of the substrate and void the EIFS Manufacturer's Warranty.

PHYSICAL PROPERTIES

Color	Clear
Odor	Kétone
Density	0.820 g/ml
V.O.C. (SCAQMD Test Method)	80 g/L
Type	Synthetic blend
Viscosity	30 – 60 cPs
Solids per weight	10% – 12%
Drying time (Depending on the temperature of the surface, the air movement, the porosity of the material and the thickness of the application)	15 min. @ 41°F (5°C) 10 min. @ 59°F (15°C) 6 min. @ 77°F (25°C) 3 min. @ 95°F (35°C)
Solvent	Acetone
D.O.T. Label	Flammable
Flash Point (Pensky-Martin Closed Cup)	-0.4°F (-18°C)

COVERAGE

- 500ml / 10m²
 - 800 Ft² / gal
- *Will vary depending on substrates porosity.

METHOD OF USE

All surfaces must be clean and dry, free of any greasy material, frost, or any other contaminants. Clean the surfaces beforehand with ADSEAL CLEANER 6003 and allow the product to evaporate for 20 minutes before applying the primer. Apply the ADSEAL PRIMER MK60095 with a clean brush or other applicator. The primer

ADSEAL PRIMER MK60095**EB PRIMER**

should thoroughly wet the surface before application of the ADSEAL silicone or hybrid sealant. Let it dry until there is no transfer to the touch. The primer should be applied to the surfaces within one hour before sealant application to avoid contamination with water, dirt, or other contaminants. If this period is exceeded, repeat the procedure above.

Refer to [ADSEAL PRIMERS Guide](#) for more information.

PACKAGING

- 500ml can

STORAGE

ADSEAL PRIMER MK 60095 has a shelf life of 12 months when stored in its unopened original packaging in a dry place at a temperature below 25 ° C (77 ° F).

CAUTION

ADSEAL PRIMER MK60095 is extremely flammable. Use caution when handling Always consult SDS (Safety Data Sheet) before using the product. Apply usual hygienic rules. Always test the product on your application before use. For industrial use only. For more information, please contact your technical representative.

IMPORTANT**READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.