

ADSEAL BACKER ROD 2600
SOFT TYPE BACKER ROD**DESCRIPTION**

ADSEAL BR 2600 is a soft, non-gassing, pliable, bi-cellular backup material for construction joints and application that require sealants. It performs as depth control for ADSEAL hybrid and silicone sealants and also helps the sealant to assume the optimum hour-glass shape. Sealants will not adhere to it; no bond breaker is required.

COMPOSITION AND MATERIALS

ADSEAL BR 2600 is a round grey, extruded bi-cellular polyethylene backer rod with a water resistant outer skin. It is compatible with cold applied cold apply sealants such as silicone, hybrid or latex acrylic.

SPECIFIC USES

Especially suited for applications with irregular and varying joint widths where standard closed cell backer rods are not appropriate and where bubbling concerns are critical. May also be used in place of standard closed-cell backer rod in most applications. Common applications include expansion and contraction joints, window glazing, curtain wall construction partitions, parking decks, bridge and highway construction pavement maintenance and log home chinking.

INSTALLATION

Joint or opening must be free of all contaminants (including curing compounds and form-release agents), loose materials, dry and free of frost. Install between 25%-50% compression. With a blunt instrument or roller, seat the ADSEAL BR 2600 to depth recommended by Adfast.

LIMITATIONS

Do not use with hot applied sealants. Sealant compatibility should be confirmed by Adfast. ADSEAL BR 2600 should be installed with a roller or flat-sided tools. Avoid puncturing stretching and over compression. Temperature limits: -90°F to 190°F (-67°C to 87°C).

ADSEAL BACKER ROD 2600

SOFT TYPE BACKER ROD

PACKAGING

ADSEAL BR 2600 is available in a wide variety of diameters and comes in 3 carton sizes. Please see the following chart details on packaging.

Diameter	Carton sizes	details	Recommended joint width
3/8" (10 mm)	18.5" x 18.5" x 15"	2100' / carton, 2 spools / carton	3/16" to 1/4"
5/8" (16 mm)	19" x 19" x 30"	1550' / carton, 2 spools / carton	3/8" to 1/2"
7/8" (22 mm)	19" x 19" x 30"	850' / carton, 1 spool / carton	1/2" to 3/4"
1-1/8" (29 mm)	19" x 19" x 30"	500' / carton, 1 spool / carton	3/4" to 7/8"
1-1/2" (38 mm)	13.5" x 13.5" x 73"	396' / carton, 6 pieces	7/8" x 1-1/4"
2" (51 mm)	13.5" x 13.5" x 73"	228' / carton, 6 pieces	1-1/4" to 1-1/2"
2-1/2" (63 mm)	13.5" x 13.5" x 73"	144' / carton, 6 pieces	1-1/2" to 2"
3" (76 mm)	13.5" x 13.5" x 73"	102' / carton, 6 pieces	2" to 2-1/2"
4" (102 mm)	13.5" x 13.5" x 73"	54' / carton, 6 pieces	2-1/2" x 3"

TECHNICAL DATA

ADSEAL BR 2600 is chemically inert and will resist gasoline, oil, and most solvents. Product will not stain or adhere to sealants.

Property	Value	ASTM Test Method
Density	1.6 – 2.0 lbs/ft ³	D 1622
Outgassing (number of bubbles)	0	C 1253
Compression recovery	> 97%	D 5249
Water absorption	< .03 grams / cc	C 1016 – Procedure B
Tensile strength	25 – 50 psi	D 1623

Meets or exceeds requirements of ASTM C1330 type B.

WARRANTY

Product is sold without warranty. In no case will Adfast be liable of incidental or consequential damages on the product. Buyer must make their own determination as to the suitability of the product and application.

ADSEAL BACKER ROD 2600
SOFT TYPE BACKER ROD**IMPORTANT****READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.