

ADSEAL 4000A2
AEROSOL SILICONE LUBRICANT**DESCRIPTION**

ADSEAL 4000A2 is an aerosol silicone lubricant. It is used as an anti-adhesive, lubricant or to facilitate the movement of parts.

PHYSICAL PROPERTIES

Specific gravity	0.7157 à 0.72 @ 20°C (68°F)
Color	Clear liquid
Solids by weight	6.25% - 6.35%
Solids by volume	4.8% - 5%
Flash point	Less than 0°C (32°F)

APPLICATION

- Doors and windows
- Woodworking
- Lubricant of moving machinery parts
- Anti-adhesive

METHOD OF USE

Spray the ADSEAL 4000A2 on the parts to be lubricated. Avoid contaminating parts that will need to be painted.

PACKAGING

- 400 grams can

STORAGE

12 months in the original unopened containers from date of manufacturing. Protect form freezing.

CAUTION

Always consult sds before using the product. Apply usual hygienic rules. Always test the product on your application before use. For industrial use only. For more information, please contact your technical representative.

ADSEAL 4000A2
AEROSOL SILICONE LUBRICANT**IMPORTANT****READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.