

ADBOND AL30316 Emulsion based adhesive

DESCRIPTION

ADBOND AL30316 is an emulsion based adhesive designed for bonding decorative laminate to wood products.

PHYSICAL PROPERTIES

Color	Blue or pink
Viscosity	3000 – 3200 cPs
Solids	55% - 57%
рН	4.0 – 5.5
Specific gravity	1.08 g/cm3

APPLICATION

ADBOND AL30316 can be applied with squeeze bottle, brush, roller, pneumatic gun or mechanical roller coater.

SUGGESTED USE

- Hot press application
- Postforming

STORAGE

6 months form date of production, in the original unopened containers. Protect form freezing. Keep in a hermetic closed container to avoid any contamination.

PACKAGING

- 200 liter drum
- 1000 liter tote tank

CLEANING

Unusable adhesive and wash water is classified as industrial liquid waste and must not be sewered or sent to municipal landfill without pre-treatment. Clean adhesive equipment with high pressure water spray to minimize water usage. Review local disposal regulations to determine optimum method for effluent pre-treatment.



ADBOND AL30316 Emulsion based adhesive

CAUTION

Always consult SDS (Safety Data Sheet) before using the adhesive. For industrial use only. For more information, please contact your technical representative.

IMPORTANT

READ CAREFULLY

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.