

ADBOND 3017-2LV
Polyvinyl acetate adhesive**DESCRIPTION**

ADBOND 3017-2LV is a low viscosity polyvinyl acetate adhesive formulated for wood dowel application. It is also commonly used on flexo folder gluer (glue-lap) and for general packaging applications of papers, cartons and corrugate. ADBOND 3017-2LV is characterized by fast setting and easy cleaning.

PHYSICAL PROPERTIES

Color	White
Viscosity	1400 – 1800 cPs
Solids	53% - 55%
pH	4.0 – 5.5
Specific gravity	1.08 g/cm ³
Shelf life	Minimum of 6 month in the original unopened container when stored in a cool dry area

APPLICATION

ADBOND 3017-2LV can be applied with squeeze bottle, roller, extrusion, pneumatic gun or mechanical roller coater. For roller coater application, apply 9-14 mils wet film thickness. The typical assembly time is dependent on the temperature as well as the thickness of the adhesive film.

SUGGESTED USE

- Wooden furniture assembly by dowel
- Flexo folder gluer (glue-lap)
- General assembly of paper and carton

STORAGE

6 months from date of production, in the original unopened containers. Protect from freezing. Keep in a hermetic closed container to avoid any contamination.

PACKAGING

- 20 liters pail
- 200 liters drum
- 1000 liters tote tank

CLEANING

Unusable adhesive and wash water is classified as industrial liquid waste and must not be sewered or sent to municipal landfill without pre-treatment. Clean adhesive equipment with high pressure water spray to minimize water usage. Review local disposal regulations to determine optimum method for effluent pre-treatment.

CAUTION

Always consult SDS (Safety Data Sheet) before using the adhesive. For industrial use only. For more information, please contact your technical representative.

IMPORTANT
READ CAREFULLY

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.