

ADSEAL 4000-100-10
SILICONE BASED LUBRICANT**DESCRIPTION**

ADSEAL 4000-100-10 is a silicone and mineral spirit based lubricant. It is used as an anti-adhesive, lubricant or to facilitate the movement of parts.

PHYSICAL PROPERTIES

Specific gravity	0.78 @ 20°C (68°F)
Color	Clear liquid
Solids by volume	10%
Flash point	54°C (129°F)

METHOD OF USE

Apply the ADSEAL 4000-100-10 by spray using a pneumatic equipment or with a brush on the parts to be lubricated. Avoid contaminating parts that will need to be painted.

PACKAGING

- 18.9 liters pail
- 200 liters drum

STORAGE

12 months in the original unopened containers from date of manufacturing. Protect from freezing.

CAUTION

Always consult SDS (Safety Data Sheet) before using the product. Apply usual hygienic rules. Always test the product on your application before use. For industrial use only. For more information, please contact your technical representative.

IMPORTANT**READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.