

ADSEAL CF 1070 SERIES
Crack filler latex acrylic sealant**DESCRIPTION**

ADSEAL CF 1070 SERIES is a water based latex sealant used for filling gaps in frames, baseboards, mouldings or any other space that needs filling. Because of some shrinkage during drying, a second layer can be necessary. It can be sanded after hardening. It offers a good adhesion on wood, mdf, metals and gypsum. It can generally be painted after a drying period of 2 hours at normal room temperature.

LIMITATIONS

- Not for immersion joints
- Not for outside applications
- Avoid contact with products that are very acidic or alkaline
- Not for horizontal joints in traffic areas
- Not for movement joints

PHYSICAL PROPERTIES

Unvulcanised	
Consistency	paste
Color	white
Density	1.57 g/ml
Solids	80% - 82%
pH	8.0 – 9.0
Hardness (shore A)	65
Skin formation	30 minutes
Can be painted	After 2 hours
Shelf life	24 months

SURFACE PREPARATION

Materials must be free of dust, greasy substances and other contaminants. Clean surfaces with ADSEAL CLEANER 6003. Let evaporate for 20 minutes before applying ADSEAL CF 1070 SERIES.

METHOD OF USE

ADSEAL CF 1070 SERIES can be easily applied with a manual caulking gun. ADSEAL CF 1070 SERIES must be shaped with the ADSEAL TOOLING KIT before skin formation. Before drying, the product can be cleaned with warm water.

PACKAGING

- 304 ml cartridge

ADSEAL CF 1070 SERIES
Crack filler latex acrylic sealant**STORAGE**

Store in its original unopened container, in a dry area and at a temperature below 25°C (77°F). The expiration date is indicated on every container. If the stored product is passed its expiration date, it doesn't automatically mean that the product cannot be used. In this case, the properties of the product must be verified in order to ensure quality. Please contact our technical service.

PRECAUTIONS

Please refer to the Safety Data Sheet (SDS) before use. Follow the usual rules of hygiene. Always test the product on the receiving application before applying to a larger area. For industrial use only. For more information, please contact your technical representative.

IMPORTANT**READ CAREFULLY**

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESS WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.